

CITIZEN

Citizen PD22

The ultimate in compact,
ultra-portable printing



2-inch wide portable receipt printing

Light weight and ultra compact, just 250 grams

Infrared IrDA and RS232C serial interfaces as standard

Uses standard AA-type batteries

Better. Believe It.®

P O R T A B L E P R I N T E R S

Citizen PD22

Citizen's PD series of portable printers are designed to be the ultimate in portable printing. Whether your application is printing receipts for customers, packing lists for products or messages sent to your telephone, the PD series of printers are ideal partners.

Fast And Quiet

The high-speed thermal head of the PD22 printer allows printing at up to 1.5 inches per second. In other words, it can print an 6-inch, 150mm long receipt in just four seconds but with only the slightest murmur from the printer.



Incredibly Light Weight

Weighing in at just 112 grams for the printer and with a total operational weight of less than 250 grams, the PD22 has to be one of the smallest and lightest printers in the world.



Using standard "AA" size batteries makes the printer flexible and easy to use as alkaline batteries are available from virtually any shop.

Alternatively, rechargeable NiCd or NiMH batteries are available from your local supplier for added convenience.

Clamshell Media Loading

Media loading on the PD22 is equally easy with the clamshell mechanism - simply drop in the roll of paper and close the cover.



Connectivity and compatibility

The PD22 features industry standard RS232C serial interface and IrDA infra-red interfaces. Both are compatible with a vast range of data sources, from handheld PCs, notebooks, mobile phones to industrial laser scanner terminals and can be used in a wide range of applications from receipt printing to stock control.

	PD-22
Technology	Direct thermal
Resolution	203 dpi, 8 dots / mm
Printhead	384 dots
Print Width Media Width	48 mm 58 mm
Print Speed (1 ply mode) Approximate speed	300 dotlines/sec 1.5 inches/sec
Mechanism type	Clam shell
Integral Paper Roll	30 mm outside diameter Approximately 10m linear length
Media Types	Roll, cut sheet, multi-copy paper
Interfaces	IrDA 1.0 Serial RS232C up to 115,200 bps
Emulations	ESC/P, Citizen original and ESC/POS (barcode commands only)
Input Buffer	64 Kb
User Interface	2 keys, 2 LEDs
Dimensions (W x D x H)	78 x 108 x 35 mm
Total Weight * - Printer - Paper roll holder - Batteries - Full paper roll	240 g 112 g (integral with printer) 93 g 35 g
Battery Type	4 x AA cells Alkaline, NiCd, NiMH
Operating Temperature Humidity Storage	0°C to +45°C (guaranteed print quality) 30% to 90% RH -25°C to +60°C
Head Life	50 million pulses, 30 Kms
Options & Accessories	RS232 cable Roll paper Spare battery set [†] Battery charger [†] Soft case [†]

* All weights are approximate and subject to source of media supplies or batteries

[†] Please consult with your supplier for exact specification & requirements for these parts

Citizen Systems Europe UK

Park House, 643 - 651 Staines Road

Feltham, Middlesex, TW14 8PA, United Kingdom

Tel: +44(0)20 8893 1900 Fax: +44 (0)20 8893 0080

Citizen Systems Europe GmbH

Mettinger Straße 11, D-73728 Esslingen, Deutschland

Fon: +49(0) 711 3906 420 Fax: +49 (0)711 3906 405

sales@citizen-europe.com www.citizen-europe.com

Supplier Details