

# STYLISH AND INNOVATIVE 4 INCH RECEIPT/LABEL PORTABLE PRINTER

## LK-P41

- High gloss cover and 3 color LEDs
- Adjustable paper width from 50.4mm to 112mm
- 2 types of battery selectable - 2200/4400mAh
- Large capacity, paper rolls up to 56mm(OD)
- Highly reliable Bluetooth communications or Wi-Fi(802.11b/g) available(Optional)
- ESC/POS, CPCL command compatible
- IP54(with case) certified



### ● SPECIFICATION

<b>PRINT METHOD</b>		Direct Thermal
<b>PRINTING SPEED (max)</b>		80mm/sec
<b>DOT DENSITY</b>		203DPI
<b>DOT PITCH</b>		8 dots/mm, 0.125pitch
<b>EFFECTIVE PRINTING WIDTH</b>		104mm, 832dots/line
<b>PAPER</b>	TYPE	Thermal paper / Label
	WIDTH	50.4mm ~ 112mm
	THICKNESS	0.06mm ~ 0.16mm
	ROLL DIAMETER	Max. Ø 56.0mm
	ROLL CORE INNER DIAMETER	12.5mm ± 0.5mm
<b>RELIABILITY</b>	TPH LIFE	50km
	PULSE ACTIVATION	50,000,000pulse or more
<b>FONTS and GRAPHICS</b>	STANDATD FONTS	Seven resident. fonts 12-48 pt.
	OPTIONAL	International character sets
	GRAPHICS, LINE AND BOX DRAWING	PCX and Bitmap
<b>BARCODE</b>	EAN-8, EAN-13, Code 39, ITF, UPC-A, UPC-E, Codabar, Code 93, Code 128, PDF 417(2D), QR Code(2D), Maxicode(2D)	

<b>EMULATION</b>	ESC/POS, CPCL Command compatible	
<b>DRIVER</b>	Windows Printer Driver(7, XP, 2000, 2003, VISTA, 32 & 64bit), Windows(CE 4.2 & 5.0 / Mobile 5.0-), Linux Printer Driver, Symbian, Blackberry, Android (2.1-)	
<b>SENSOR</b>	Paper end / Black mark / Gap / Cover open sensors	
<b>INTERFACE</b>	STANDARD	Serial(RS-232C), USB
	OPTION	Bluetooth class 2, Wi-Fi(802.11b/g)
<b>BATTERY CHARGER</b>	External Charger(Output 8.4VDC / 0.8A)	
<b>BATTERY</b>	7.4V 2200mAh, 3.7Hrs charging time, 20Hrs stand-by	
<b>DIMENSION</b>	WxDxH(mm)	149 x 162 x 70
	WxDxH(inch)	5.87 x 6.37 x 2.75
<b>WEIGHT</b>	572g (with 2200mAh Battery)	
<b>TEMPERATURE</b>	OPERATION	-10 ~ 50°C
	STORAGE	-20 ~ 60°C
<b>HUMIDITY</b>	OPERATION	35 ~ 95 %
	STORAGE	10 ~ 95 %

### ● APPLICATION

