

SEWOO has POS printer line to suit for point of sales application and needs in marketplace.

SLK-TS400

- Compact size
- Top & Front exit available
- Easy Replacement of Components (Tool-less)
- ESC/POS command compatible
- Jam free design -Wall mount installation available



Application

RETAIL



SUPERMARKET





COSMETIC STORE







HOTEL

AIRPORT

COUPON

RESTAURANT

TICKET



AMUSEMENT PARK TICKET



ADMISSION TICKET

ENTRANCE TICKET









www.miniprinter.com

3INCH THERMAL PRINTER SLK-TS400

PRINTING SPECIFICATION

PRINTING

METHOD	Direct Thermal
SPEED	220mm/sec
WIDTH	72mm
RESOLUTION	180 DPI

BARCODE

1D	Code 11, Code39, Code 93, Codebar,ISBT-128, UPC-A, UPC-E, EAN-8. EAN-13, Code128 with subsets A/B/C, Interleaved 2-of-5
2D	PDF417,QR Code, DATA MATRIX

PAPER SPECIFICATION	
TYPE	Receipt
WIDTH	80mm
THICKNESS	0.065mm
ROLL DIAMETER	Ø83mm

INTERFACE



STANDARD	USB
OPTION	Serial(RS-232C, 25pin), Ethernet

HARDWARE SPECIFICATION

POWER	
ТҮРЕ	External SMPS
AC	100 ~ 240Vac 50/60 Hz
DC	24Vdc / 1.75A

SENSOR

Paper End, Cover Open

RELIABILITY

TPH LIFE	150Km
AUTO CUTTER	1,500,000 cuts(Guillotine)

CASH DRAWER

DKD (Cash Drawer) 1Port

• All specification and desings are subject to change without notice.

5ewoo

SEWOO TECH CO., LTD.

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 447-210 Republic of Korea TEL +82-31-8077-5000 FAX +82-31-459-8880 E-Mail : sales@miniprinter.com

DRIVER

Windows Driver(2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Windows CE & Mobile Driver & SDK(CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1 ~) SDK, Windows SDK

EMULATION

ESC/POS Command compatible

ACCESSORIES (OPTION)

Melody Box, Wall Mount

DIMENSION

WxDxH

130 x 140 x 154 (mm)

KEY FEATURES

COMPACT SIZE

The Comparison of size between SLK-TS400 and Smartphone







FRONT EXIT

EASY LOAD

BARCODE



_(()

AUTO CUTTE

*Front exit is available with a wall mounted.

R

>>~~~~~~~~~~>>

HIGH SPEED



m ()

PAPER WIDT